



REICU

Rec-Send

RSM232 Series

Features :

- Operating voltage: 3.3V/5.0V
- I/O-Isolation 2500 VDC
- Baud rate : 115.2Kbps
- Instantaneous bus over voltage protection
- Compatible with EIA/TIA-232-F standard
- No External Components Required
- Low EMI
- High electromagnetic anti-interference
- Operating temperature : -40 ~ +85

**DESCRIPTION**

RSM232 is the single transceiver which integrates with the power isolation and electrical isolation. It realizes with isolated RS-232 separation circuit, the isolation voltage is up to 2500VDC. It improves bus reliability and common mode noise immunity. It is built-in TVS tube, which increases the chip prohibit the bus from overvoltage capability. The minimum transmission rate of data transmission is 12.Kbps. The product design meets the standard of EIA/TIA-232-F, and with ESD (in HBM mode) up to +15KV the protection ability. It is small and high integration, no need peripheral circuit, easy to use.

Model Selection Guide

Order Code	Input Voltage		Baud rate(Kbps)	Speciality	Package
	Vin(VDC)	Range(VDC)			
RSM232	5	3.0-5.5	115.2	Sing RS232	DIP8

Parameter

Item	Specification	Min	Typ	Max	Units
Input Voltage		3.0	5.0	5.5	VDC
Operating Temperature		-40		+85	
Storage Temperature		-55		+125	
Isolation voltage		2500			VDC
Isolation capacitance		40			pF
Humidity	No frosting	10		95	%
Quiescent Current				33	mA
Propagation delay time		350		400	μS
TXD/RXD pin current			3		mA
Receiver input voltage		-15		+15	V
Transceiver output voltage range		-5		+5	V
Transceiver short-circuit current			70		mA
ESD Protection	Contact model			±4000	V
	Machine model			±200	V

REV:13.3

Page 1 of 2

www.reicu.com

E-mail:service@reicu.com






REICU

Rec-Send

RSM232 Series

Application**Application Area****Typical Circuit**

- Industrial automation system
- Automatic control on electrical power system
- Cartronics
- Communication
- Access control system & Monitor
- PLC controller

**Mechanical Dimension****Bottom View****Lateral View**

Units : mm (inch)
Tolerances : ±0.25mm (±0.01inch)

Pin Connections

Pin	Function	Description
1	+Vin	positive pole
2	GND	negative pole
3	Tin	TTL/CMOS transmitter input
4	Rout	TTL/CMOS receiver output
6	Rin	RS232 receiver input
7	Tout	RS232 transmitter output
8	R-GND	RS232 power isolated ground

REV:13.3

Page 2 of 2

www.reicu.com

E-mail:service@reicu.com